



## Window Air Conditioner Cooling Only

Available in 8, 10 & 12K BTU  
Fits Standard Double Hung Windows  
2016 ENERGY STAR® Certified

### Specifications

Voltage	115 VAC
Frequency	60 Hz
Plug	Prewired LCDI NEMA Type
Control Panel	Digital Display & Interface
Temperature Display	Fahrenheit or Celsius
Timer Settings	Up to 24 Hours
Fan Speeds	High/Medium/Low
Refrigerant	Eco-Friendly R-410A
Filter	Reusable
Directional Air Louvers	4-Way Manual Control
Fresh Air Vent	Available on Some Models
Wireless Remote	Included
Installation Hardware	Included

### Mode Selection

Choose between fan, cooling, dehumidifying & automatic operation.

### Sleep Feature

Slowly increases room temperature by 4°F when activated and returns to the original temperature setting after 7 hours.

### Energy Saver Feature

Optimally manages system operation to minimize power consumption.

### Follow-Me Feature

Automatically adjusts thermostatic performance based on location of the remote.

### Check Filter Indicator

Light illuminates to notify when the filter needs to be cleaned or replaced.

### Auto-Restart

If power loss occurs, the system will automatically resume operation based on previous settings.

### Optimal Conditions for Cooling

- Outdoor Temperature: 64-109°F
- Indoor Temperature: 62-90°F

### Certifications

- C-UL-US
- 2016 ENERGY STAR®
- CEC & DOE Listed

### Warranties

- 1-Year Limited Warranty on Entire Unit
- 5-Year Limited Warranty on Sealed System

### Accessories & Replacement Parts

- 2472207 - Replacement Remote Control (8k model use 2472208)



NEMA Receptacle Configuration.



5-15P

For Compatibility, Match to NEMA Plug.

Garrison Model #	2498534	2498535	2498536
<b>Cooling Performance</b>			
Capacity (BTU/Hr)	8,000	10,000	12,000
Current	5.9 A	7.5 A	8.7 A
Input Power	666 W	833 W	1,000 W
Refrigerant Charge Amount	16.23 Oz.	19.05 Oz.	22.58 Oz.
Design Pressure (High/Low)	520/300 PSIG	520/300 PSIG	520/300 PSIG
<b>General Performance</b>			
EER	12	12	12
Airflow CFM (H/M/L)	224/208/185	285/257/232	300/270/244
Room Area	300-350 Ft. <sup>2</sup>	400-450 Ft. <sup>2</sup>	450-550 Ft. <sup>2</sup>
Max. Indoor Sound Level	60 dBA	60 dBA	61 dBA
Dehumidification Rate	2.1 Pt./Hr	2.3 Pt./Hr	2.5 Pt./Hr
Fresh Air Vent Control	No	Yes	Yes
<b>Electrical Specifications</b>			
Voltage	115 VAC	115 VAC	115 VAC
Frequency	60 Hz.	60 Hz.	60 Hz.
NEMA Plug Configuration	5-15P	5-15P	5-15P
Power Cord Length	6-1/2 Ft.	6-1/2 Ft.	6-1/2 Ft.
<b>Dimensions</b>			
Net Weight	51 Lbs.	63 Lbs.	71 Lbs.
Window Opening Width	23" to 36"	23" to 36"	23" to 36"
Window Opening Height	14" Min.	15-1/2" Min.	15-1/2" Min.
A	13-1/2"	14-5/8"	14-5/8"
B	18-1/2"	19"	19"
C	17-1/2"	21-1/2"	21-1/2"

All Dimensions are Nominal.

